GroovJoint Product Line

Stainless Steel Grooved Fittings

- Designed to reduce labor costs in the field by using the grooved method for the installation of piping systems.
- Grooved Fittings are produced in Sch. 10 and Sch. 40 pipe thicknesses. The size range for Sch. 10 stainless steel is 1" - 24" roll groved in both 304L and 316L grades. In Sch. 40 stainless steel, the range is 1" - 12" in both 304L and 316L. The Sch. 40 product line includes both roll grooved and cut grooved ends. The product line also includes stainless steel flange adaptors in Sch. 10 and Sch. 40 material in 304L and 316L grades.
- Stainless Steel Grooved Fittings Products include:

Duplex Couplings

Ductile Iron

Couplings

Flexible Couplings

- Butterfly Valve

– 90° Elbows

- 45° Elbows

- 111/4° Elbows

Rigid Couplings
- 22½° Elbows

Concentric Reducers

- Eccentric Reducers

Tees

- Reducing Tees

- End Caps

- Flange Adaptors



Fabrication

- GroovJoint manufactures a variety of stainless steel custom fabrications and specialty fittings designed to the customer's needs.
- Specialty products include (but are not limited to):
 - Grooved Laterals & Wyes
 - Large Diameter Grooved Reducing Tees
 - 3D Grooved Flbows
 - Grooved Spool Pieces
 - Grooved to Press and Grooved to Threaded Fittings
- We are versatile and specialize in stainless steel. We are a <u>one-stop shop</u> when it comes to all your fittings needs!











Stainless Steel Press Style Fittings

- **Press End Fittings** are offered in a wide range of sizes and configurations (1/2" 2") compatible with both Sch. 5 and Sch. 10S stainless steel pipe. The PressJoint fitting method allows easier installation than traditional welded or threaded piping methods. It can be used in a wide range of applications.
- These are the main applications of our system: compressed air, heating facilities, sanitation facilities, fire-extinguishing system (sprinkler), solar energy, plumbing, industrial facilities, shipping facilities and mining.
- PressJoint Stainless Steel Pressed Fittings Products include:
 - Couplings
 - Slip Couplings
 - 90° Elbows
 - 90° Street Elbows
 - 45° Elbows
 - 45° Street Elbows
 - Transition Nipple

- Tees
- Reducing Tees
- Reducing Tee w/FPT Branch
- Fitting by Press Adaptor
- Female Adaptors
- Male Adaptors
- Van Stone Flg Adaptors

- End Caps
- Flange AdaptorsPress x Flg
- Unions Press x Press
- Ball Valve Press x Presses
- Weld Adaptors
- Gaskets offered include: EPDM, NBR (Buna), and Viton.













Milwaukee M18[™] Force Logic Long Throw Press Tool

 There is a corresponding, easily exchangeable jaw for each diameter, which is placed in the tool cylinder. The pressfitting tool has a battery.





Corporate Office: 155 North Wacker Drive, Suite 4250 Chicago, IL 60606

312-803-2627 – Phone sales@groovjoint.com www.groovjoint.com

Place distributor label here